DID-5P3

Impact Drivers

(pistol and standard)



- Double hammer type
- Controllable the rotation direction by one hand
- High productivity due to light weight, compact design, and easy handling grip for operator
- Two stage trigger control RPM Quiet operation with a silencer
- Quiet operation with a silencer
- Rear exhaust

| Model | Hex size | | Bolt size | Max, free speed | Max, torque | | Length | | Weight | | Thread air inlet | | | Noise | Recommended air pressure | |
|---------|----------|------|-----------|-----------------------|-------------|-----|--------|-----|--------|-----|------------------------|------|-----|-------|-----------------------------|---|
| | | | | | | | | | | | | | | | | |
| DID-5P3 | 1/4 | 6.35 | M5-M8 | 12,000 | 17 | 167 | 5.98 | 153 | 2 | 0.9 | PT1/4 | 10.5 | 0.3 | 90 | 85 | 6 |

DID-6P3

Impact Drivers

(pistol and standard)



DID-6P3

- Double hammer type
- High productivity due to light weight, compact design, and easy handling grip for operator
- Quick changeable driver anvil
- Specially used in the field of automobile and motorcycle assembly line or maintenance
- Rear exhaust

| Model | Hex size | | Bolt size | Max, free speed | Max, lorque | | Length | | Weight | | Thread air inlet | Average air consumption | | Noise | Recommended air pressure | |
|---------|----------|------|-----------|-----------------------|-------------|-----|--------|-----|--------|-----|------------------------|-------------------------|--------|-------|-----------------------------|--------|
| | in | mm | size | RPM | kg.m | N,m | in | mm | io | kg | | 117/min | n'/min | dB | PSI | kg/cm² |
| DID-6P3 | 1/4 | 6.35 | M5-M8 | 10,000 | 21 | 206 | 7.0 | 178 | 2.4 | 1.1 | PT1/4 | 10.5 | 0.3 | 95 | 85 | 6 |